

DRC-9-04x12-D-ZP-D BK

Part Number: F904804M5B

Applications: Blown Installation, CATV and DataCom, Long Distance OSP, Outdoor Plant Duct Installation

General Construction: This gel free cable contains 48 SM G652D color-coded optical fibers in 4 color-coded loose tubes, each tube containing 12 fibers. The tubes include a swellable yarn to prevent the ingress of water and are SZ stranded with one filler around a dielectric central strength member. Swellable fiber-glass strength yarns reinforce the cable core and an outer jacket completes the cable structure.



Outer Jacket Material: PE
Outer Diameter: 10 mm nom.
Weight: 75 kg/km

Design & Materials

Buffer Material:	Polypropylene
Tube Diameter:	2.5 mm nom.
Conductor Color Code:	Fiber Color Code:
Central Strength Member:	FRP
Cabling:	SZ
Strength Elements:	E-Glass Yarns
Fiber Containing Tubes:	4
Number of fibers:	48
Waterblocking:	Dry Waterblocking
Rip-Cord:	Yes
Outer Jacket Color:	Black
Marking:	Teldor Standard

Standards

Applicable Standards:	IEC 60794, ISO/IEC 11801-1, TIA/EIA-568, ASTM G154, RoHS-2 2011/65/EU
Installation:	Guidelines as per IEC TR 62691

Performance

Tensile Strength - Short Term:	2700 N max.
Tensile Strength - Long Term:	1600 N max.
Impact Resistance:	4.4 N*m
Impact Resistance:	3 cycles
Max. Crush Resistance:	400 N/cm
Min. Bend Radius for Installation:	20xD mm
Min. Bend Radius for Operation:	10xD mm
Repeated Bending:	25 cycles
Max. Operating Temperature:	+70 °C
Min. Operating Temperature:	-40 °C
Max. Storage Temperature:	+70 °C
Min. Storage Temperature:	-40 °C
UV Resistance:	Yes
Waterblocking:	Yes

Prepared By	Revised By	Version Num	Modified on
teldor.com	Yigal Piness	1.7	30-11-2015

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500

ISRAEL

Tel: +972 4 6770555

Fax: +972 4 6770650